

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : AAP AHS CERAMIC SEAL_1GL_4CT

Material number : V35724

Manufacturer or supplier's details

Company : NCS Vehicle Care, Inc.

Address : 1997 American Blvd.
De Pere, WI 54115

Telephone : 877-326-9274

Emergency telephone numbers

For SDS Information : www.ncsvehiclecare.com

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear

GHS Classification

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Corrosion

Exclamation
mark

Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Fatty acids, coco, reaction products with diethylenetriamine and soya fatty acids, ethoxylated, chloromethane-quaternized	68604-75-1	>= 20 - < 30
decamethylcyclopentasiloxane	541-02-6	>= 10 - < 20
2-butoxyethanol	111-76-2	>= 10 - < 20
propan-2-ol	67-63-0	>= 5 - < 10
2-chloroethanol	107-07-3	>= 1 - < 3
alpha-hexylcinnamaldehyde	101-86-0	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
Take off contaminated clothing and shoes immediately.
If skin irritation persists, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Rinse immediately with plenty of water, also under the eyelids,

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

	for at least 15 minutes. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration, contact time). Causes serious eye damage. Causes skin irritation. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Water spray Dry chemical Alcohol-resistant foam Carbon dioxide (CO2)
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx) Smoke Chlorine compounds Silicon oxides Sulphur oxides
Specific extinguishing methods	: Do not allow run-off from fire fighting to enter drains or water courses.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours or spray mist.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Prevent unauthorized access.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.
Keep away from food and drink.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
decamethylcyclopentasiloxane	541-02-6	TWA	10 ppm	US WEEL
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL

SAFETY DATA SHEET**AAP AHS CERAMIC SEAL_1GL_4CT**

Version 1.4

Revision Date 05/20/2022

		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
2-chloroethanol	107-07-3	C	1 ppm	ACGIH
		C	1 ppm 3 mg/m3	NIOSH REL
		TWA	5 ppm 16 mg/m3	OSHA Z-1
		C	1 ppm 3 mg/m3	OSHA P0
		C	1 ppm 3 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200.mg/g Creatinine	ACGIH BEI
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

Hand protection	
Material	: Protective gloves
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: clear
Odour Threshold	: No data available
pH	: 6 - 7
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93.3 °C
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Density	: 0.94 g/cm ³ (40 °C)
Solubility(ies)	
Water solubility	: completely soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: 15 mm ² /s (40 °C)

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration, contact time). Causes serious eye damage. Causes skin irritation. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	Confirmed animal carcinogen with unknown relevance to humans
OSHA	2-butoxyethanol 111-76-2 No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute oral toxicity	: Acute toxicity estimate : 2,372 mg/kg Method: Calculation method
---------------------	---

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

Acute inhalation toxicity : Acute toxicity estimate : 20.98 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 2,529 mg/kg
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg
Method: Calculation method

2-chloroethanol:

Acute oral toxicity : LD50 Oral Rat: 71 mg/kg

Acute inhalation toxicity : LC50 Rat: 290 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal Rabbit: 67 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Components:

alpha-hexylcinnamaldehyde:

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

propan-2-ol :

Partition coefficient: n-octanol/water : log Pow: 0.05

alpha-hexylcinnamaldehyde :

Partition coefficient: n-octanol/water : log Pow: 4.686

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

+ B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
chloromethane	74-87-3	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2-chloroethanol	107-07-3	500	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation

SARA 302 : The following components are subject to reporting levels established by SARA Title III, Section 302:
2-chloroethanol 107-07-3 1.7036 %

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:
2-butoxyethanol 111-76-2 14.9607 %

California Prop. 65



WARNING: This product can expose you to chemicals including chloromethane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	3
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms

:



Corrosion



Exclamation
mark

Signal word

: **Danger:**

Hazard statements

: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

Precautionary statements

:

Prevention: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

SAFETY DATA SHEET

AAP AHS CERAMIC SEAL_1GL_4CT

Version 1.4

Revision Date 05/20/2022

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.4
Revision Date:	05/20/2022

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.